

# Stratasys J850 Prime

The J850 features multiple versatile, multimaterial 3D printers powered by PolyJet Technology

Whether you need full-color consumer product prototypes or multimaterial models for functional testing, the J8 Series offers the perfect 3D printing solution. The Stratasys J850™ Prime 3D printer deliver unrivaled aesthetic results with full-color capability including texture mapping and color gradients. This lets you create prototypes that look and feel like real products, and accurately show design intent in color, material and finish.



## J850 Prime Printer and Material Specifications

<b>Model Materials</b>	<ul style="list-style-type: none"> <li>• Vero™ family of opaque materials including neutral shades and vibrant VeroVivid™ colors</li> <li>• Agilus30™ flexible material</li> <li>• Transparent VeroClear™ and VeroUltraClear</li> <li>• Digital material</li> <li>• VeroUltra™ White/Black</li> </ul>
<b>Digital Model Materials</b>	<p>Unlimited number of composite materials including:</p> <ul style="list-style-type: none"> <li>• Over 500,000 colors</li> <li>• Digital ABS Plus and Digital ABS2 Plus in ivory</li> <li>• Rubber-like materials in a variety of Shore A values</li> <li>• Translucent color tints</li> </ul>
<b>Build Size</b>	90 x 390 x 200 mm (19.3 x 15.35 x 7.9 in.)
<b>Layer Thickness</b>	Horizontal build layers down to 14 microns (0.00055 in.) 55 microns (0.002 in.) in Super High Speed mode
<b>Network Connectivity</b>	LAN - TCP/IP
<b>System Size and Weight</b>	1400 x 1260 x 1100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (948 lbs.)
<b>Operating Conditions</b>	Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30–70% (non-condensing)
<b>Power Requirements</b>	100–120 VAC, 50–60 Hz, 13.5 A, 1 phase 220–240 VAC, 50–60 Hz, 7 A, 1 phase
<b>Regulatory Compliance</b>	CE (low-voltage and EMC directive), FCC, EAC, cTUVus, FCC, KC, RoHs, WEEE, Reach, RCM
<b>Software</b>	GrabCAD Print
<b>Build Modes</b>	High Quality: up to 7 base resins, 14-micron (0.00055 in.) resolution High Mix: up to 7 base resins, 27-micron (0.001 in.) resolution High Speed: up to 3 base resins, 27-micron (0.001 in.) resolution Super High Speed: 1 base resin, 55 micron (0.002 in.) resolution
<b>Accuracy</b>	Typical deviation from STL dimensions, for models printed with rigid materials, based on size: under 100 mm – ±100µ; above 100 mm – ±200µ or ± 0.06% of part length, whichever is greater.

**Additive Manufacturing Centre**  
Chadwick House, Woodyard Lane,  
Foston, Derby, DE65 5BU

+44 01283 585955

[sys-uk.com](http://sys-uk.com)



**GET IN TOUCH**  
[www.sys-uk.com/contact](http://www.sys-uk.com/contact)