

Stratasys Origin One

A transformative 3D printer enabling mass production of end-use parts in a diverse range of high-performance materials. Achieve industry-leading accuracy, consistency, detail and throughput with Programmable PhotoPolymerization P3™ technology.



General

Technology	Programmable PhotoPolymerization P3
Materials	Photocurable materials from Stratasys ecosystem material partners. Refer to SYS website for an up-to-date selection
Build Envelope (XYZ)	192 x 108 x 370 mm / 7,672 cm ³ (7.5 x 4.25 x 14.5 in. / 462 in ³) Maximum length on the diagonal — 220 mm (8.6 in.)
Minimum Feature Size	Material and design dependent, as low as 50µm
Resolution	4K light engine
Process Energy	UV (385nm) and thermal
Pre-Print Software	GrabCAD Print or optional 3rd party solutions
Regulatory Compliance	CE, FCC, KC, RCM

Physical Footprint

System Size and Weight	49.6 x 60.1 x 119.1 cm (19.5 x 23.6 x 46.8 in.) 81 kg (180 lbs.)
-------------------------------	---

Facility Requirements

Power Requirements	100-240 VAC, 50/60Hz, 7.1A, 1 Ph or 200-240 VAC, 50/60 Hz, 3.5 A, 1 Ph
Network Connectivity	Ethernet / Offline connectivity available with Origin One Local
Ventilation	Refer to photopolymer material MSDS or contact Stratasys rep for guidelines.
Operating Conditions	Operating temperature 15°C to 30°C (59°F to 86°F) Operating Humidity 30% to 70%
Gas Exhaust (optional)	Facility exhaust

Material Handling

Resin Tray Capacity	2L
Resin Storage Temp	Typically 15°C to 30°C (59°F to 86°F)

Optional Add-Ons

On-Premise	Origin One Local
Air Extraction	ProAero

Additive Manufacturing Centre
 Chadwick House, Woodyard Lane,
 Foston, Derby, DE65 5BU

+44 01283 585955

sys-uk.com



GET IN TOUCH
www.sys-uk.com/contact